

# DH351

High resolution presentations



- **Lights on viewing – 3600 ANSI Lumens**
- **Easy connectivity – HDMI, USB Power**
- **Portable and lightweight**
- **Built in audio**

The Full HD 1080p HD15 projector is ideal for watching live sport, TV shows or movies any time of day. You can even connect your games console and play games on it with its low input latency. Convenient and easy to set up this bright and versatile projector also boasts Amazing colour technology and conforms to Rec.709 delivering accurate true to life colour reproduction.



## Specifications

<b>Display/image</b>	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	3,600 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Uniformity	80%
Screen size	0,71m ~ 7,65m (28" ~ 301") diagonal
<b>Lamp info</b>	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
<b>Optical</b>	
Throw ratio	1,47:1 ~ 1,62:1
Projection distance (m)	1m - 9,8m
Zoom	1,1
Zoom type	Manual
Focal length (mm)	15.59 ~ 17.14
Native offset	116%
<b>Connectivity</b>	
Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support <b>Outputs</b> 1 x Audio 3.5mm, 1 x USB-A power 1.5A
<b>General</b>	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	5W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro, WHD200
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	205W
Power consumption (max)	295W
<b>Weight and dimensions</b>	
Net weight	2,8kg
Dimensions (W x D x H) mm	316 x 244 x 108

