

ML750e

Ultra-compact LED projector









- HD Ready and LED technology Great for movies, gaming and PC-free presentations
- Great connectivity HDMI, MHL, micoSD and built in speaker
- Built in media play and optional wireless presentations
- Compact & Lightweight < 0.4kg

The ML750e ultra-compact portable LED projector is easily transportable between your home and office. This tiny projector weights less than 0.4kg and comes with a convenient carry bag. Watch HD movies, play video games or even present that winning presentation, the ML750e has everything you need to impress your audience.



Specifications

Power consumption (min)

Power consumption (max)

Dimensions (W x D x H)

Net weight

Weight and dimensions

2.5
DLP
WXGA (1280x800)
700 LED brightness
20,000:1
16:10
4:3,16:9
+/-40°
15.375 ~ 91.146Khz
24 ~ 85(120 for 3D)Hz
85%
0.43m ~ 2.54m (17" ~ 100") (diagonal)
LED
20,000 hours
1.5:1
0.55m - 3.23m
Fixed
14.95
100%
010
Institute of the LIDAM of the CD annual and the Mills of the resistance CD
Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card, 1 x USB-A reader
Outputs 1 x Audio 3.5mm
Odipato 1 X Addio otomini
30dB
FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) SVGA 120Hz, XGA 120Hz
SVGA 120Hz, XGA 120Hz 3D ready
SVGA 120Hz, XGA 120Hz 3D ready
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish,
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Attitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control Battery
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control Battery Basic user manual
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control Battery
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control Battery Basic user manual 16.00ms
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control Battery Basic user manual
SVGA 120Hz, XGA 120Hz 3D ready Security bar, Kensington Lock, Password protected interface 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 1W Carry bag Universal I/O cable AC power cord Remote control Battery Basic user manual 16.00ms

16W

26W

0.38kg 105 x 106 x 39



