

# W340UST

Ultra short throw projector



- **Bright WXGA projector - 4000 ANSI lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **Ultimate control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Feature packed - Four corner adjustment, Office viewer, optional wireless presentations**



## Specifications

<b>Display/image</b>	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	4,000 Lumens
Contrast ratio	22,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-4°
Keystone correction - vertical	+/-4°
Horizontal scan rate	15.375 ~ 91.147Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	2.16m ~ 2.92m (85" ~ 115") diagonal
<b>Lamp info</b>	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
<b>Optical</b>	
Throw ratio	0.27:1
Projection distance (m)	0.49m - 0.66m
Zoom type	Fixed
Focal length (mm)	3.72
Native offset	118%
<b>Connectivity</b>	
Connections	<p><b>Inputs</b> 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 2 x USB-A reader/wireless</p> <p><b>Outputs</b> 1 x VGA, 1 x Audio 3.5mm</p> <p><b>Control</b> 1 x RS232, 1 x RJ45</p>
<b>General</b>	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	16W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200, WUSB
<b>Networking</b>	
LAN - control	Yes
LAN - display	Yes
LAN - wireless networking	Yes - optional
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	200W
Power consumption (max)	275W
<b>Weight and dimensions</b>	
Net weight	3.9kg
Dimensions (W x D x H) mm	343 x 383 x 112

