optoma.nl



ZU820TST

Ultra bright professional installation laser projector



- 8200 lumen DuraCore laser projector Ultra bright for immersive installations
- Full motorised lens shift Ideal for a simple set-up
- Large zoom range Motorised zoom expands placement opportunities
- DuraCore laser technology Delivers 30,000 hours of virtually maintenance-free operation

At 8200 lumens with 4K and HDR compatibility, the ZU820TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorised zoom and focus, full motorised lens shift, and built-in dual 10W speakers.



High brightness, colour precision and quiet operation, alongside a 1.26x zoom, make this projector the ideal solution for a variety of enduser scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.

Specifications

UPC: 796435 44 628 4, EAN: 5055387666672, Colour: Black	
	55387666672, Colour: Black
Display/image	
Display technology	
Resolution	WUXGA (1920x1200)
Brightness	8.200 lumens
ANSI brightness	6.900
Contrast ratio	3.000.000:1
Contrast ratio - full on/off	1.100:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction -	30°
norizontal	
Keystone correction - vertical	15°
Displayable colours (millions)	1073.4
Jniformity	95%
Screen size	1.27m ~ 7.62m (50" ~ 300") diagonal
	Alexini - Alozini (oo - 000) diagonar
amp info	Looor
Light source type	Laser
ASER life	30.000 hours
Optical	
Throw ratio	0.75:1 ~ 0.95:1
Projection distance (m)	0.79m - 6.21m
loom	1.26
loom type	Motorised
Focal length (mm)	11.11 ~ 14.16
ens shift	Vertical: +/-50%, Horizontal: +/-15%
ens shift	Yes - {{downloads link}}
Connectivity	((
Connections	Investe 1 v. UDDeseT 1 v. UDMI 0 0, 1 v. UDMI 1 4s 0D
Johneodona	Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D
	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm
	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A,
	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm
	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x
	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm
AN - wireless networking	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x
	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232
aeneral	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232
General Noise level (typical)	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No
General loise level (typical) loise level (max)	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB
General Joise level (typical) Joise level (max) JD	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D
General Joise level (typical) Joise level (max) 9D Security	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock
General Noise level (typical) Noise level (max) SD Security P rating	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X
General Joise level (typical) Joise level (max) JD Security P rating	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese,
General Noise level (typical) Noise level (max) ND Security P rating DSD / display languages	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
General loise level (typical) loise level (max) D Becurity P rating JSD / display languages 4/7 operation	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes
Reneral loise level (typical) loise level (max) D Decurity Prating DSD / display languages 4/7 operation 60° operation	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes
General Joise level (typical) Joise level (max) JD D Security P rating DSD / display languages 14/7 operation 160° operation Remote control	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote
Aeneral loise level (typical) loise level (max) D ecurity P rating JSD / display languages 4/7 operation 60° operation temote control	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes
Reneral loise level (typical) loise level (max) D becurity P rating DSD / display languages 4/7 operation 60° operation Remote control Speaker count	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote
Aeneral loise level (typical) loise level (max) D Decurity Prating DSD / display languages 4/7 operation 60° operation Remote control speaker count Vatts per speaker	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2
Aeneral loise level (typical) loise level (max) D eccurity Prating DSD / display languages 4/7 operation 60° operation Remote control speaker count Vatts per speaker letworking	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2
ieneral loise level (typical) loise level (max) D ecurity Prating ISD / display languages 4/7 operation 60° operation lemote control peaker count /atts per speaker letworking AN - wireless networking	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 No
eneral oise level (typical) oise level (max) D ecurity P rating SD / display languages 4/7 operation 50° operation emote control peaker count /atts per speaker etworking AN - wireless networking AN	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W
ieneral oise level (typical) oise level (max) D ecurity P rating SD / display languages 4/7 operation 60° operation emote control peaker count /atts per speaker letworking AN - wireless networking AN	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W
Aeneral loise level (typical) loise level (max) D ecurity P rating VSD / display languages 4/7 operation 60° operation 60° operation lemote control ispeaker count Vatts per speaker letworking AN - wireless networking AN Power iower supply	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input
Aeneral loise level (typical) loise level (max) D becurity P rating DSD / display languages 4/7 operation 60° operation Remote control ippeaker count Vatts per speaker Jetworking AN Power Power consumption (standby)	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W
General Joise level (typical) Joise level (max) JD Security P rating OSD / display languages 14/7 operation 660° operation Remote control Speaker count Vatts per speaker Jetworking AN - wireless networking Yower Yower consumption (standby) Yower consumption (min)	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes Backlit ProAV remote 2 00W No Yes Backlit ProAV solv 60 Hz with PFC input 0.5W 260W
General Joise level (typical) Joise level (max) JD Security P rating OSD / display languages (4/7 operation (60° operation Remote control Speaker count Vatts per speaker Jetworking AN - wireless networking AN Power Power consumption (standby) Power consumption (min) Power consumption (max)	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W
Aeneral Ioise level (typical) Ioise level (max) D becurity P rating OSD / display languages 4/7 operation 60° operation Remote control iopeaker count Vatts per speaker Jetworking AN - wireless networking AN Power Yower consumption (standby) Yower consumption (min) Yower consumption (max)	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes Backlit ProAV remote 2 00W No Yes Backlit ProAV solv 60 Hz with PFC input 0.5W 260W
Aeneral Ioise level (typical) Ioise level (max) D becurity P rating OSD / display languages 4/7 operation 60° operation Remote control Speaker count Vatts per speaker Jetworking AN - wireless networking AN Yower consumption (standby) Power consumption (min) Power consumption (max) Veight and dimensions	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes Backlit ProAV remote 2 00W No Yes Backlit ProAV solv 60 Hz with PFC input 0.5W 260W
AN - wireless networking General Noise level (typical) Noise level (max) BD Security P rating DSD / display languages 24/7 operation 860° operation 80° operation 8	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock IP5X 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlitt ProAV remote 2 10W No Yes Backlitt ProAV remote 2 0W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W 260W 520W







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 29042023065413